

# REZONTECH FLAME DETECTOR

THE BEST SOLUTION FOR FIRE DETECTION SYSTEM





# REZONTECH FLAME DETECTOR

Designed and manufactured in South Korea, under Rezontech's technology and the own strict quality control system with international laboratories such as FM, ATEX, CCCF, IECEX, KFI(Korea Fire Institute) and so on. This expertise and responsibility for quality will make Rezontech meet all your needs from the fire detection.

Rezontech Co., Ltd. is the world-class Flame Detector Manufacturer has been leading Flame Detector market in Korea since 2004.

We developed first-ever UV/IR & Triple IR type Flame Detectors in Korea with own unique technology.

Rezontech keeps growing with continuous R&D for fire detection technology. Thus we acquired 20 global certificates and approvals on Flame Detectors and exported it over 50 countries in the world. We are proud to supply state of the art Flame Detectors along with the Automatic Gas Suppression system to the industry leading sites & military facilities to protect human life & asset from the fire disaster.

We will conquer the global market based on our continuous effort, know-how & reliability with the best service and best quality.





## PRINCIPLE

The Rezontech flame detector can promptly analyze sensory inputs from the ultraviolet and infrared light sources emitted by a flame to alert against fires.

IR3 flame detection sensing three specific wavelength bands within the Infrared spectral region that are algorithmically analyzed. UV/IR flame detector uses UV/IR wavelength signals comparing to detect fire and minimizes false alarm.

Flame detectors are less spatial and environmental constraints such as outdoor high ceilings of industrial sites, where ordinary heat/smoke detectors cannot be used.



## ADVANTAGES

### Economical Effect

Providing an economical solution by long and wide detection range

### Explosion-Proof

Achieved international certificates to be used in hazardous areas

### False alarm immunity

Highly precise and responsive detection using our own unique algorithm

### Early Fire detection

Flame Detector can detect fire typically within 5 seconds using optical Ultraviolet and Infrared sensors

### Fast Delivery

Best efforts to the faster delivery to satisfy our valuable customers

### Easy installation

Simple and easy Installation for anyone and any site



## APPLICATION

- Oil & Gas Facilities
- Iron & Steel Facilities
- Power Station
- Chemical Facilities
- Shipyards
- Petrochemical Plant
- Refineries
- Semi-Conductor Facilities
- UNESCO World Heritage
- Historical Site

# UV/IR FLAME DETECTOR

## RFD - 2000X

**Type** | UV/ IR  
**Model** | RFD-2000X  
**Detection Range** | 98.5ft(30m)  
**Field Of View** | H90° V90°  
**Operating Temperature Range** | -40°C to +75°C  
**Humidity Range** | Up to 95% relative humidity

**Enclosure Material** | SUS 316  
**Dimenton** | W134 H117 D120mm  
**Weight** | 3.2kg  
**Response** | Typically 5 seconds

### ELECTRICAL SPECIFICATION

**Operating Voltage** | 24 VDC (17 VDC to 32 VDC)  
**Power Consumption** | 1.8W maximum at 32VDC  
**Output** | Relay Contacts (Fire, Fault, Warning Alarm)  
 4-20mA Current Output  
 RS-485 Proprietary Communication  
**Conduit Entry Size** | 2 x 1/2" NPT, M20 X 1.5 inch

### APPROVALS

**Performance** | FM3260  
**Explosion-Proof** | FM Class I Division 1 Groups B, C and D, Class II Division 1 Groups E, F and G, Class III, ATEX/IECEx Ex db IIB + H2, T6  
**Protection** | IP67, NEMA Type 4X



## RFD - 2000

**Type** | UV/ IR  
**Model** | RFD-2000  
**Detection Range** | 98.5ft(30m)  
**Field Of View** | H90° V90°  
**Operating Temperature Range** | -40°C to +75°C  
**Humidity Range** | Up to 95% relative humidity

**Enclosure Material** | Aluminum Alloy  
**Demention** | W150 H125 D103mm  
**Weight** | 1.8kg  
**Response** | Typically 5 seconds

### ELECTRICAL SPECIFICATION

**Operating Voltage** | 24 VDC (17 VDC to 32 VDC)  
**Power Consumption** | 1.8W maximum at 32VDC  
**Output** | Relay Contacts (Fire, Fault, Warning Alarm)  
 4-20mA Current Output  
 RS-485 Proprietary Communication  
**Conduit Entry Size** | 2 x 1/2inch PF.

### APPROVALS

**Performance** | FM3260  
**Protection** | IP67, NEMA Type 4X



## RFD - 2FTN

**Type** | UV/ IR  
**Model** | RFD-2FTN  
**Detection Range** | 98.5ft(30m)  
**Field Of View** | H100° V100°  
**Operating Temperature Range** | -40°C to +75°C  
**Humidity Range** | Up to 95% relative humidity

**Enclosure Material** | Aluminum 6061  
**Demention** | W64 H64 D75mm  
**Weight** | 0.53kg  
**Response** | Typically 5 seconds

### ELECTRICAL SPECIFICATION

**Operating Voltage** | 24 VDC (17 VDC to 32 VDC)  
**Power Consumption** | 5.8W maximum at 32VDC  
**Output** | Relay Contacts (Fire, Fault, Warning Alarm)  
 4-20mA Current Output  
 RS-485 Proprietary Communication  
**Conduit Entry Size** | 1/2 inch NPT

### APPROVALS

**Performance** | CCCF, KFI  
**Explosion-Proof** | ATEX, NEPSI, EX-GOST  
 ATEX Ex db IIC T6 / T5 Gb  
 ATEX Ex tb IIIC T85 °C / T95 °C Db  
**Protection** | IP66, IP67

# TRIPLE IR & HYDROGEN FLAME DETECTOR



## RFD - 3000X

**Type** | IR3  
**Model** | RFD-3000X  
**Detection Range** | 197ft(60m)  
**Field Of View** | H90° V90°  
**Operating Temperature Range** | -40°C to +75°C  
**Humidity Range** | Up to 95% relative humidity

**Enclosure Material** | SUS 316  
**Dimenton** | W134 H117 D112mm  
**Weight** | 4kg  
**Response** | Typically 5 seconds

### ELECTRICAL SPECIFICATION

**Operating Voltage** | 24 VDC (18 VDC to 30 VDC)  
**Power Consumption** | 4.5W maximum at 30VDC  
**Output** | Relay Contacts (Fire, Fault, Warning Alarm)  
 4-20mA Current Output  
 RS-485 Proprietary Communication  
**Conduit Entry Size** | 2 x 1/2" NPT, M20 X 1.5 inch

### APPROVALS

**Performance** | FM3260, CCCF, KFI  
**Explosion-Proof** | FM Class I Division 1 Groups B, C and D Class II Division 1 Groups E, F and G Class III, ATEX/IECEx/NEPSI Ex db IIB + H2, T5  
**Protection** | IP66, IP67, NEMA Type 4X



## RFD - 3000

**Type** | IR3  
**Model** | RFD-3000  
**Detection Range** | 197ft(60m)  
**Field Of View** | H90° V90°  
**Operating Temperature Range** | -40°C to +75°C  
**Humidity Range** | Up to 95% relative humidity

**Enclosure Material** | Aluminum Alloy  
**Demention** | W150 H103 D125mm  
**Weight** | 1.7kg  
**Response** | Typically 5 seconds

### ELECTRICAL SPECIFICATION

**Operating Voltage** | 24 VDC (18 VDC to 30 VDC)  
**Power Consumption** | 4.5W maximum at 30VDC  
**Output** | Relay Contacts (Fire, Fault, Warning Alarm)  
 4-20mA Current Output  
 RS-485 Proprietary Communication  
**Conduit Entry Size** | 2 x 1/2 inch PF

### APPROVALS

**Performance** | FM3260, CCCF  
**Protection** | IP67, NEMA Type 4X

### Hydrogen Flame Detector



## RFD - 2000X-H

**Type** | UV/IR & Hydrogen  
**Model** | RFD-2000X-H  
**Detection Range** | 98.5ft (30m) for n-Heptane fire  
 15ft(4.5m) for Hydrogen fire (30 inch plume)  
**Field Of View** | H90° V90°  
**Operating Temperature Range** | -40°C to +75°C  
**Humidity Range** | Up to 95% relative humidity

**Enclosure Material** | SUS 316  
**Demention** | W134 H117 D120mm  
**Weight** | 3.2kg  
**Response** | Typically 5 seconds

### ELECTRICAL SPECIFICATION

**Operating Voltage** | 24 VDC (17 VDC to 32 VDC)  
**Power Consumption** | 1.8W maximum at 32VDC  
**Output** | Relay Contacts (Fire, Fault, Warning Alarm)  
 4-20mA Current Output  
 RS-485 Proprietary Communication  
**Conduit Entry Size** | 2 x 1/2" NPT, M20 X 1.5 inch

### APPROVALS

**Performance** | FM3260  
**Explosion-Proof** | FM Class I Division 1 Groups B, C and D Class II Division 1 Groups E, F and G Class III, ATEX Ex db IIB + H2, T6  
**Protection** | IP67, NEMA Type 4X



# TEST LAMP & ACCESSORIES

## FLAME DETECTOR TESTER

Rezontech test lamp is designed to test our flame detector within 30 seconds by producing particular frequencies at UV and IR radiation. Our test lamp is able to safely test in a hazardous areas without using actual fire.

## TEST LAMP

### TL-3000

- Operation Distance | 3m (Max. 5m)
- Target Model | RFD-3000 and RFD-3000X
- Operation Time | Max. 3.5 hours
- Dimension & Weight | About 3.2kg / 250mm X 145mm
- Enclosure | Aluminium (Anodizing Process)
- Temperature Range | Operating : 0°C to 50°C  
Storage : -10°C to 60°C












### TL-205

- Operation Distance | 3m (Max. 5m)
- Target Model | UV/IR flame detector
- Operation Time | Max. 2hours
- Dimension & Weight | About 3.2kg / 250mm X 145mm
- Enclosure | Aluminium (Anodizing Process)
- Temperature Range | Operating : 0°C to 50°C  
Storage : -10°C to 60°C



## PRODUCT LINE-UP

Category	Model Name	Specification			Photos	Approvals	
		Type	Range	Field of View		Performance	Explosion Proof
FM Approval Flame Detector	RFD-2000	UV / IR	30m	90°		FM	-
	RFD-2000X	UV / IR	30m	90°		FM	FM ATEX IECEX
	RFD-2000X-H	UV / IR	30m	90°		FM	FM ATEX
	RFD-3000X	IR3	60m	90°		FM CCCF KFI	IECEX FM, ATEX NEPSI (CNEX)
	RFD-3000	IR3	60m	90°		FM CCCF	-
KFI Approval Flame Detector	RFD-2FTN	UV / IR	30m	100°		CCCF KFI	ATEX NEPSI EX-GOST
	RFD-2TN	UV / IR	30m	100°		KFI	-
	RFD-3FT	IR3	50m	90°		KFI	KGS
	RFD-3T	IR3	50m	90°		KFI	-


## ACCESSORIES



BK-01



BK-02



RSC-05



RSC-02

## THE BEST SOLUTION FOR FIRE DETECTION SYSTEM

### REZONTECH

72-9 Beolmal-ro, Dongan-gu, Anyang-si,  
Gyeonggi-do, South Korea

Tel. + 82-31-348-4246~8

Fax. +82-31-348-3004

E. [sales@rezontech.com](mailto:sales@rezontech.com)

Web. [www.rezontech.com](http://www.rezontech.com)