




GLOBAL SEALING SYSTEMS INC.
<http://www.global-sealing.kr>

RUBBER PUNCHED STRIP SEALS


Manufacturing Facilities

GSSK has equipped machines in workshops including:
water-jet cutting machines, strip cutting machines, hand cutting etc.



MSA Certification Co., Ltd.
Quality Management System Certificate
ISO 9001:2008
Certificate Number : KorQ-118832





PLEASE SPECIFY


Material
Size
Thickness
Hole
Length&Width

RUBBER PUNCHED STRIPPING SEALS

GLOBAL SEALING SYSTEMS is Rubber Rolls & Rubber Molded Parts producing and selling company. One of our main products, Rubber Punched Strip Seals are slit-to-width rolls of rubber with holes punched at precise uniform intervals, perfectly suited to sealing between bolted or riveted panels of medium to large sized tanks. GSSK equipped to manufacture virtually any type of rubber, any width, and any holes size or spacing configuration.

* Typical application

Door seals for silos and tank to provide sealing for products such as sugar, flour, oils, chemicals and other all kinds of contents.





Available Materials

GSS Rubber Punched Strip Seals are available in the following materials (Popular varieties include Neoprene RUBBER PUNCHED STRIP SEALS impression for general purpose.)

Nitrile Rubber (Buna-N)

- ▶ Used for petroleum products
- ▶ White Nitrile (FDA approved)
→ good for general purpose food and medical products storage.

EPDM

- ▶ Superior weather resistance
- ▶ Economical general purpose tank sealing material.

Silicone rubber

- ▶ Suitable for both low and high temperature extremes as well as food and medical products.


Viton

- ▶ Suitable for both high temperatures and chemically volatile environments.

Various non-rubber gasket sheeting materials

- ▶ sponge rubber, foam, plastic etc.

Available Sizes




Thickness

Average thickness for punching is between 1/16" ~ 1/14" (1.6mm~6.4mm) for most tank sealing applications. However this is not a limitation and GSS easily apply the same processes to thinner and thicker varieties of rubber and other materials.

Hole Shapes, Size, and Spacing

GSS can manufacture any holes pattern, and can even supply oval, square, or alternate shaped holes. Of course, all rubber materials are available in slit-to-width rolls without any holes, as well.



*Double
punched hole*

Seal Length, Width

Tank stripping is usually sold by uncut roll size, which varies by thickness and variety between 25 and 300 foot lengths. Naturally, we can generally cater to special requirements on Roll length.

Dimensional Tolerances

Tolerances vary according to material and dimension specifications, but typically runs around $\pm .015$ inches on Key dimensions like width and hole diameter.

Contact us

Kerry Rhee / CEO. President
kerry@global-sealing.kr

Ellie Lee / Int'l Business Dept. / General Manager
ellie@global-sealing.kr

Jenny Kim / Overseas Sales / Assistant Manager
jenny@global-sealing.kr

GLOBAL SEALING SYSTEMS INC.

7F. Intellium-Centum B/D 1458 U-dong Haeundae-gu, Busan, 612-020 Korea
<http://www.global-sealing.kr> TEL : 82-51-932-1001~3 FAX : 82-51-932-1006